

| You are in: [Lozier](#) > [Products](#) > [Powered Transport Flex Conveyor](#)

# Powered Transport Flex Conveyor

Part Number: **CYT**



Lozier's powered Transport Flexible Conveyor provides a durable and efficient solution for your loading and unloading needs. The Transport Flexible Conveyor expands and contracts for easy mobility and storage and includes adjustable variable speed settings from 0-120 feet per minute.

## Product Details:

- Width: 30"
- Height: 32" - 36" (adjustable in 2" increments)
- Length: Varies based on number of sections
- Variable Speed: 0-120 ft/min
- Roller Spacing: 3", 4", 5" on center
- Capacity: 100 lbs per linear foot
- IP54: Resistant to dust, ingress, and brief water exposure

## Product Options and Numbers

---

Example Part #: **CY T 30 B 10**

Conveyor: **CY**

Style: T

Width: 30"

Roller Spacing: B,C, D

Number of Sections:3, 4, 5, 6, 7, 8, 9, 10

Suffix Key

- T - Transport
- B - 3" On Center
- C - 4" On Center
- D - 5" On Center

Length and Expansion Ratio				
Roller Spacing	No. of Sections	Expanded Length	Contracted Length	Expansion Ratio
3" On Center	2	6' 1"	4' 7"	1.56
	3	9' 1"	6' 5"	1.60
	4	12' 1"	8' 4"	1.62
	5	15' 1"	10' 3"	1.64
	6	18' 1"	12' 2"	1.65
	7	21' 1"	14' 0"	1.65
	8	24' 1"	15' 11"	1.66
	9	27' 1"	17' 10"	1.66
	10	30' 1"	19' 8"	1.67
4" On Center	2	7' 11"	4' 7"	1.88
	3	11' 11"	6' 5"	1.96
	4	15' 11"	8' 4"	2.01
	5	19' 11"	10' 3"	2.04
	6	23' 11"	12' 2"	2.06
	7	27' 11"	14' 0"	2.07
	8	31' 11"	15' 11"	2.08
	9	35' 11"	17' 10"	2.09
	10	39' 11"	19' 8"	2.10

5" On Center	2	9' 9"	4' 7"	2.15
	3	14' 9"	6' 5"	2.27
	4	19' 9"	8' 4"	2.34
	5	24' 9"	10' 3"	2.39
	6	29' 9"	12' 2"	2.42
	7	34' 9"	14' 0"	2.44
	8	39' 9"	15' 11"	2.46
	9	44' 9"	17' 10"	2.47
	10	49' 0"	19' 8"	2.48

Widths		
Nominal	Actual Roller	Overall Conveyor
30"	29"	36.5"

Box Size		
Roller Spacing	Maximum Width	Minimum Length
3" on center	30	6"
4" on center	30	8"
5" on center	30	10"

Electrical	
Voltage	120VAC single phase
Rating	UL508A
Connectors	
AC Power	NEMA 5-20
Infeed End	Modular heavy duty female
Outfeed End	Modular heavy duty male
BUS	
Power	480 W
Data	N/A

Safety	Category 1
--------	------------